

PRODUCT DATA SHEET

PE NDB Nail Sealing Tape DSK

Is a double-sided adhesive PE foam tape that is used as nail-seal tape in the area of the counter battens. Tested for protection from rain by the Austrian Wood Research Association, (Holzforschung Austria Order no. 203/2003/2 T/HH).

**FIELD OF APPLICATION**

- Nail seal for roof underlays minimum roof pitch $\geq 5^\circ$

ADVANTAGES

- easy to use
- good adhesion on wood and underlays
- the 60 mm tape can be used with the nail-seal tape dispenser

AVAILABLE IN THE FOLLOWING DIMENSIONS


Type	DSK	DSK	DSK
Roll width	60 mm	70 mm	80 mm
Roll length	30 m	30 m	30 m
Carton content	8 Rolls	7 Rolls	6 Rolls

PRODUCT DATA

Material composition	Closed cell polyethylene foam double-sided adhesive
Thickness	3 mm
Colour	Green
Density	30 kg/m ³
Temperature resistance - Standard	-40 °C - 80 °C
Working temperature	5 °C - 40 °C
Storage	Cool and dry
Water consumption (7d)	< 1 Vol.%

PE NDB Nail Sealing Tape DSK

Attach PE NDB Nail Sealing Tape ESK/ DSK to the roof sheeting directly beneath the counter-batten. The standards according to ÖNORM B 4119 and/or ZVDH (Central Association of German Roofers) must be observed.



ISOCELL GmbH & Co KG

Gewerbestraße 9
5202 NEUMARKT AM WALLERSEE | Österreich
Tel.: +43 6216 4108 | Fax: +43 6216 7979
office@isocell.at

ISOCELL SCHWEIZ AG

Herbergstrasse 29
9524 Zuzwil | Suisse /Schweiz
Tel.: +41 71 940 06 72
office@isocell.ch

ISOCELL FRANCE

170 Rue Jean Monnet | ZAC de Prat Pip Sud
29490 GUIPAVAS | France
Tél.: +33 2 98 42 11 00 | Fax: +33 2 98 42 11 99
contact@isocell-france.fr

ISOCELL BUREEL BELGIË

Außenborner Weg 1 | Schoppen
4770 Amel | Belgique
Tel.: +32 80 39 90 58 | Fax: +32 80 39 97 68
office@isocell.be

ISOCELL Sverige AB

Köpsvängen 10
168 67 BROMMA | Sverige
Tel.: +46 10 130 25 00
info@isocell.se

ISOCELL
www.isocell.com