

mdm nt sp. z o.o. ul. Bestwińska 143 43-346 Bielsko-Biała, Poland phone: +48 33 47 94 402 fax: +48 33 47 94 513 e-mail: office@mdmnt.com

www.mdmnt.com

NATIONAL DECLARATION OF PERFORMANCE

No. 118/2017

1. Name and trade name of the construction product:

VR rollable ridge vent

BR-Vent rollable ridge vent

Blach-vent plus rollable ridge vent

2. Construction product type:

Ridge Vent-roll

3. Intended use(s):

Rollable ridge vents are intended for ventilation of the space between roof covering and the bottom roofing layers and for protecting them against insects and intrusion of water and snow.

4. Name and address of manufacturer's head office and product manufacture location:

Manufacturer:

MDM NT sp. z o.o.

Ul. Bestwińska 143

43-346 Bielsko-Biała

manufacture location

The European Union

5. Name and address of authorised representative's head office, if any:

not applicable

6. National system used for assessment and verification of constancy of performance:

system 4

NIP: 548-26-14-481, REGON: 241562837 Numer KRS 0000354101, Sąd Rejonowy w Bielsku-Białej VIII Wydział Gospodarczy Krajowego Rejestru Sądowego Wysokość opłaconego kapitału zakładowego: 992 500 PLN Bank Handlowy w Warszawie S.A., SWIFT: CITIPLPX 67 1030 1508 0000 0008 1613 6008 (PLN) 23 1030 1508 0000 0008 1613 6024 (EUR) 98 1030 1508 0000 0008 1613 6032 (USD)

- 7. National Technical Specification:
- 7a. Polish Standard for the Product:

not applicable

Name of an accredited certification body, accreditation number and national certificate number or name of an accredited laboratory/laboratories and accreditation number:

not applicable

7b. National Technical Assessment:

ITB Technical Approval No. AT-15-5208/2013

Technical assessment body / National technical assessment body:

Instytut Techniki Budowlanej in Warsaw

Name of an accredited certification body and certificate number:

not applicable

8. Declared performance:

Essential characteristics of the construction product for its intended use(s):	Declared performance:	Remarks
Aluminium thickness [mm]	0.12-0.14	-
Varnish thickness [µm]	15-25	-
Type of adhesive	Butyl	-

9. The performance of the above-mentioned product is in conformity with the declared performance listed in point 8. This national declaration of performance is issued according to the act of April 16th, 2004 on construction products (Journal of Laws of 2014, item 883 and of 2015, item 1165), on the sole responsibility of the manufacturer indicated above.

On behalf of the manufacturer, the declaration was signed by:

Krzysztof Gęborski, Vice-president of the Board

(name and position)

Bielsko-Biała on January 2nd, 2017.

(place and date of issue)

(signature)

Krzysztof Gęborski