



PRODUCT DATA SHEET

AIRSTOP FLEX Sealing Patches

To guarantee air and wind-tightness for the skin of a construction it must have the appropriate foils or panel materials providing a permanent seal at overlaps, gaps, joints and penetration points. AIRSTOP FLEX Sealing Plaster is tear-resistant with adhesive generously applied, and is suitable for a variety of bonding applications.

FIELD OF APPLICATION

- a quick seal for larger openings e.g. blow-in openings

ADVANTAGES

- quick and easy application
- strong adhesion

STANDARDS

- DIN 4108-11
- DIN 4108-7
- ÖNORM B 8110-2
- SIA 180

AVAILABLE IN THE FOLLOWING DIMENSIONS

| | | |
|----------------|------------|------------|
| Width | 180 mm | 200 mm |
| Length | 180 mm | 200 mm |
| Piece / roll | 222 pieces | 200 pieces |
| Carton content | 4 Rolls | 4 Rolls |

PRODUCT DATA

| | |
|-----------------------------------|--|
| Material composition | Slightly expandable synthetic base material, laminated airtight, acrylate adhesive |
| Colour | White transparent with Airstop imprint |
| Temperature resistance - Standard | -40 °C - 100 °C |
| UV-resistance | 2 months |
| Working temperature | from -5 °C |
| Storage | 2 years; cool and dry |

AIRSTOP FLEX Sealing Patches

INFO

The materials used must be free from dust and grease and substrates must be dry and supporting.

The greater the pressure applied, the better the performance of the adhesive tape.

Sealing Plaster has the function of sealant and not of a firm connector (No permanent tensile stresses may act on the bonded joints — e.g. if the drill cores of OSB boards are re-inserted, they must be mechanically fixed). The pure acrylate adhesive used does not contain resins or other additives that could cause the adhesive film to become brittle and therefore this product is extremely resistant to ageing.



ISOCELL GmbH & Co KG

Gewerbestraße 9
5202 NEUMARKT AM WALLERSEE | Österreich
Tel.: +43 6216 4108 | Fax: +43 6216 7979
office@isocell.at

ISOCELL FRANCE

170 Rue Jean Monnet | ZAC de Prat Pip Sud
29490 GUIPAVAS | France
Tél.: +33 2 98 42 11 00 | Fax: +33 2 98 42 11 99
contact@isocell-france.fr

ISOCELL Sverige AB

Köpsvängen 10
168 67 BROMMA | Sverige
Tel.: +46 10 130 25 00
info@isocell.se

ISOCELL SCHWEIZ AG

Herbergstrasse 29
9524 ZUZWIL | Suisse /Schweiz
Tel.: +41 71 940 06 72
office@isocell.ch

ISOCELL BUREEL BELGIË

Außenborner Weg 1 | Schoppen
4770 AMEL | Belgique
Tel.: +32 80 39 90 58 | Fax: +32 80 39 97 68
office@isocell.be

ISOCELL
www.isocell.com