



Product first time CE-
marked: 2020

Declaration of Performance

Nr. DOP-27555HA-01A



1. Unique identification code of the product-type: 27555HA

Walki ® Active 35, 80gsm

2. Intended use:

Flexible sheets for waterproofing - Plastic and rubber vapour control layers – EN 13984:2013, Type A

3. Manufacturer:

Walki B.V.
Postbus 716
2003 Haarlem
The Netherlands

4. Authorised representative: Not applicable.

5. System/s of AVCP: System 3.

6a. Harmonised standard:

EN 13984:2013

Notified bodies:

Fraunhofer (1004), BTTG (0338) and Technicky a skusobny ustav stavebny (1301) performed an initial type test under system 3 and issued a test report

7. Declared performances:

Declared performance:				
Essential characteristics	Performance	Tolerances		Harmonised technical specification
		Minimum	Maximum	
Reaction to fire	E	-		EN 13984:2013
Resistance to water penetration	W1			
Water vapour transmission Sd (m)	17	14	20	
Sd value (m) min/max	-	0,4	45	
Tensile force, longitudinal (N/50mm)	≥100	-		
Tensile force, transverse (N/50mm)	≥100			
Elongation, longitudinal (%)	≥50			
Elongation, transverse (%)	≥60			
Tear resistance, longitudinal (N)	≥80			
Tear resistance, transverse (N)	≥80			
Durability - water vapour resistance after artificial aging	Pass			
Durability against alkali	Pass			

8. Appropriate Technical Documentation and/or Specific Technical Documentation:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with EU Regulation No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of Walki B.V.
Valkeakoski, 13th February 2020

Ann-Mari Ukkonen
Technical Service & Development Manager