

PRODUCT DATA SHEET

AIRSTOP SOLO Adhesive Tape

To guarantee air and wind-tightness for the skin of a construction it must have the appropriate foils or panel materials providing a permanent seal at overlaps, gaps, joints and penetration points. The patented special foil can be easily torn crosswise for small pieces (scaling technique at penetration points). AIRSTOP SOLO's special coating means that it can be easily pulled from the roll. This premium design saves the effort of pulling off a liner and its subsequent disposal.

FIELD OF APPLICATION

- adhesion of vapour retarders and barriers
- joins of OSB and DWD panels indoors and outdoors
- joins and connections with wood, masonry and metal

ADVANTAGES

- easily torn off
- smooth application
- promotes healthy living
- liner-free
- applied quickly
- no time wasted on disposal
- high adhesive properties

STANDARDS

- DIN 4108-7
- DIN 4108-11 including aging
- ÖNORM B 8110-2
- SIA 180

AVAILABLE IN THE FOLLOWING DIMENSIONS

Roll width	60 mm
Roll length	50 m
Carton content	10 Rolls

PRODUCT DATA

Material composition	Special foil, reinforcement fabric, acrylate adhesive
sd-value	~35 m
Temperature resistance - Standard	-40 °C - 80 °C
UV-resistance	12 months
Working temperature	-5 °C - 40 °C
Storage	2 years, cool and dry
UV-resistance uncovered	2 months

AIRSTOP SOLO Adhesive Tape

DESCRIPTION

Longitudinal tear-resistant system adhesive tape with acrylate adhesive.

UV STABILITY

max. 2 months; for higher requirements please use the 'OMEGA Facade tape'.

ADHESIVE FORCE

AIRSTOP adhesive tapes perform the function of airtight and wind-tight sealing and not that of positive bonding. Vapour barriers and other films must always be secured by staples, laths or the like (mechanical).

PLASTERING OVER

the AIRSTOP adhesive tapes cannot be plastered or painted over. Please use the AIRSTOP FLEX adhesive tape for this application.

BONDING TECHNIQUE

when affixing the adhesive tape, the tape must be adhered over its entire surface to the substrate. The higher the contact pressure, the better the adhesion (pressing roller). It is possible without problem to adhere the tape over itself or to adhere it crosswise. We recommend the AIRSTOP SPRINT Sealant or AIRSTOP DIMAROLL for plastered surfaces or very rough wood. The materials to be processed must be free of dust and grease, in addition to which the substrates must be dry and capable of bearing loads. In the case of doubt we recommend the pre-treatment of the substrate. (UNI Primer or BUBI LF Adhesive Primer).

BONDING AT VERY LOW TEMPERATURES

AIRSTOP adhesive tapes are suitable for bonding from approx. -5°C . Note please that surface condensate can result at lower temperatures even in the case of minimal changes in temperature. This acts like a separating layer and decreases the adhesion. Hot-stored tapes provide noticeably improved initial adhesion. (fan heaters, insulated containers)

ADHERES TO THE FOLLOWING SUBSTRATES

wood, wood-based panels (OSB, MDF, 3S-panels etc.), brick, plastics (smooth surface, free of silicones and waxes), metals free of oxides and rust etc.

Observe the system suggestions in accordance with our price list.

After the attachment of the AIRSTOP SOLO adhesive tape a so-called 'cross-linking process' takes place. This takes about 6 - 24 hours, depending on the temperature. Only then is the full adhesion attained. At very low temperatures, the process can be optimised with the help of UNI Spray Primer.

STORAGE

cool and dry in a closed cardboard box; do not stack rollers on top of one another without release paper in between.

DISPOSAL

release paper and adhesive tape - domestic waste, waste tip

GARANTEE

the acrylate adhesive employed does not contain any additives that cause the adhesive layer to become brittle and is therefore extremely resistant to aging.

Please refer to the respective product data sheet for the aging resistance of the respective AIRSTOP adhesive tapes.



ISOCELL GmbH & Co KG

Gewerbestraße 9
5202 NEUMARKT AM WALLERSEE | Österreich
Tel.: +43 6216 4108 | Fax: +43 6216 7979
office@isocell.at

ISOCELL SCHWEIZ AG

Herbergstrasse 29
9524 ZUZWIL | Suisse /Schweiz
Tel.: +41 71 940 06 72
office@isocell.ch

ISOCELL FRANCE

170 Rue Jean Monnet | ZAC de Prat Pip Sud
29490 GUIPAVAS | France
Tél.: +33 2 98 42 11 00 | Fax: +33 2 98 42 11 99
contact@isocell-france.fr

ISOCELL BUREEL BELGIË

Außenborner Weg 1 | Schoppen
4770 AMEL | Belgique
Tel.: +32 80 39 90 58 | Fax: +32 80 39 97 68
office@isocell.be

ISOCELL Sverige AB

Köpsvängen 10
168 67 BROMMA | Sverige
Tel.: +46 10 130 25 00
info@isocell.se

ISOCELL
www.isocell.com