

## Tape GREEN

Technical data sheet  
02040161  
Review 01\_15.05.2014

| Properties                     |  |
|--------------------------------|--|
| Roll width                     | 60 mm  |
| Roll length                    | 25 m   |
| Color                          | Green  |
| Adhesive                       | Solvent, VOC and emollient free acrylic based adhesive       |
| Thickness                      | 0,31 mm $\pm$ 5%   |
| Adhesive weight                | 190 g/m <sup>2</sup> $\pm$ 10%                               |
| Adhesive backing               | Tape with PE surface reinforced with woven polyester backing |
| Covering material              | Silicone liner (90 g/m <sup>2</sup> )                        |
| Adhesive strength (AFERA 5001) | > 25 N/25mm  |
| Application temperature        | - 40°C / + 80°C  |
| Adhesion reaction time         | Immediate / maximum adhesion in 24 hours                     |
| UV stability                   | 3 month  |
| Packaging                      | Boxes of 5 rolls   |
| Storage                        | Store in a clean dry place for a maximum of 24 months        |

All values contained in this technical data sheet, are middle values based on the series of tests in patterns. The minimal tolerance amounts  $\pm$ 5%.

The Riwega S.r.l. reserves themselves the possibility to review or change these technical values. You can find the technical data sheet on the website [www.riwega.com](http://www.riwega.com). This data sheet replaces the previous copy.