

Isocell GmbH & Co KG
Gewerbstraße 9
A-5202 Neumarkt am Wallersee
Tel +43 (0)6216 41 08 - 0
Fax +43 (0) 6216 79 79
office@isocell.at
www.isocell.com

1. Unique identifying code of the product type	OMEGA G50 Facade Lining
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4)	Mentioned on the container or the printing
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	EN 13859-2 (11.2010): Flexible sheets for waterproofing. Part 2: Underlays for walls
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	Isocell GmbH & Co KG Gewerbstraße 9 A- 5202 Neumarkt am Wallersee
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	./.
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 3
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard	Prüfung Brandverhalten: MPA Braunschweig (0761) Prüfung der Wasserdichtheit: KIWA TBU Greven (0799)
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	./.

9. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Length	50 / 50 m	
Width	1,5 / 3 m	
Weight	225 g/m ²	
Water vapour transmission properties	0.18 ± 0,03 m m	
Material composition	PES fleece with TPU coating on one side, two acrylic adhesive strips on both front and back edge	
Resistance to water flow	W1	
Elongation - lengthwise	25 %	
Elongation - crosswise	30 %	
Tear propagation resistance - lengthwise	150 N	
Tear propagation resistance - crosswise	160 N	EN 13859-2
Fire performance	B-s1, d0	
Fire performance	EN 13501-1	
After artificial aging		
Elongation - lengthwise	≥ 65%	
Elongation - crosswise	≥ 65%	
Tensile strength - lengthwise	≥ 65%	
Tensile strength - crosswise	≥ 65%	
Resistance to water flow	W1	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer by:



Spitaler Anton (Managing Director)
(Name and function)

(Signature)

Neumarkt a.W. 11/04/2023
(Place and date of issue)