

Technical data sheet

OMEGA MONO 200 Roof Underlay

is a non-vapour retardant roof underlay with two two-way acrylate adhesive strips for installation directly on the thermal insulation or the wood sheathing. The monolithic membrane guarantees high UVresistance and extremely high resistance to the penetration of rain. Vapour transmission through the functional film is no longer a result of capillary conduction but transport is active from the interior to the exterior through the non-porous membrane. Water-tightness and UV-resistance are therefore retained even under the influence of wood preservative, chain saw oil or resin. Type: Standard = without adhesive tape, SK DUO = double sided adhesive tape.

ADVANTAGES

- rain-tight, wind-tight
- 12 weeks UV-stability
- water-tight
- easy to cut
- non-glare

FIELD OF APPLICATION

- for vented pitched roofs
- high quality protection for wood and insulation
- for installation directly on thermal insulation or wood sheathing

RECOMMENDED PRODUCTS

	OMEGA QUILLI Sealing Compound
	OMEGA NDB Nail Sealing Tape DSK
	OMEGA FROZEN Adhesive Paste
	PE NDB Nail Sealing Tape DSK
	OMEGA NDB Nail Sealing Tape ESK

AVAILABLE DIMENSIONS

Article number	Type	Roll width	Roll length	Rolls / Pallet	Total area
2MONO200	Standard	1.5 m	50 m	20 rolls	1500 m ²
2MONO200W	SK DUO	1.5 m	50 m	20 rolls	1500 m ²

TECHNICAL DATA

sd-value	0.15 (±0,1) m	Material composition	monolithic membrane with PP fleece on both sides and two-way acrylate adhesive strips
Elongation (EN 12311-1) lengthwise	50-80 %	Elongation (EN 12311-1) crosswise	60-90 %
Tensile strength (EN 12311-1) lengthwise	340 (± 40) N/50mm	Tensile strength (EN 12311-1) crosswise	260 (± 40) N/50mm
Tear propagation resistance (EN 12310-1) lengthwise	210 (± 40) N	Tear propagation resistance (EN 12310-1) crosswise	280 (± 40) N
Thickness	0.7 mm	Temperature resistance	-40–80 (short-term 100 °C) °C
Weight	200 g/m ²	Colour	Grey
UV-resistance	12 weeks	Resistance to water flow (EN 1928)	W1
Storage	cool and dry	Fire performance (EN 13501-1 / EN 11925-0)	E

ISOCELL GmbH & Co KG
Gewerbstraße 9
5202 NEUMARKT AM
WALLERSEE | Österreich
Tel.: +43 6216 4108
office@isocell.at

ISOCELL FRANCE
170 Rue Jean Monnet | ZAC de
Prat Pip Sud
29490 GUIPAVAS | France
Tél.: +33 2 98 42 11 00
contact@isocell-france.fr

ISOCELL Sverige AB
Torshamnsgatan 35
164 40 KISTA | Sverige
Tel.: +46 10 130 25 00
info@isocell.se

ISOCELL SCHWEIZ AG
Herbergstrasse 29
9524 ZUZWIL | Suisse
/Schweiz
Tel.: +41 71 940 06 72
office@isocell.ch

ISOCELL BUREEL BELGIË
Außenborner Weg 1 | Schoppen
4770 AMEL | Belgique
Tel.: +32 80 39 90 58
office@isocell.be

ISOCELL


WWW.ISOCELL.COM



OMEGA MONO 200 Roof Underlay


(1) UNDERLAY (UNSUPPORTED)

OMEGA Roof Underlay is nailed parallel to the eaves with a slight drape and laid and mechanically fixed above the rafters. Vertical overlaps/joins must always lie on a rafter. All overlaps must be bonded with OMEGA QUILLI Sealing Compound. Horizontal underlay panels can be joined using SK DUO adhesion as provided or with OMEGA QUILLI Sealing Compound.



(2) UNDERLAY (SUPPORTED)

OMEGA roof underlay is laid on sheathing parallel to the eaves. The blankets are fixed with concealed nails spaced at 10 cm at the ridge-side edges (marks at edge). All overlaps/joins must be bonded with OMEGA QUILLI Sealing Compound (without applying pressure) or the integrated adhesive strips (applying adequate pressure). For the raintight version (temporary cover) a nail-seal under the counter batten (OMEGA QUILLI Sealing Compound or OMEGA NDB Nail Sealing Tape) is necessary. The single-sided nail-seal tape must be attached to the roof underlay directly beneath the counter batten!




(3) EAVES CONSTRUCTION

We recommend an eaves construction with drainage below the gutter so that snowmelt build-up can easily drain off. We recommend the use of a metal sheet to drain off water.


(4) RIDGE AREA

The ridge area is closed directly when covered with OMEGA roof underlay. This provides immediate protection against water penetration. In non-insulated lofts and/or ventilated interior insulation the ridge formation must be made open: the blankets end 3 cm before the ridge apex, counter battens are mounted and a 50 cm wide strip of OMEGA roof underlay must be attached over the roof apex.



(5) VALLEY INFORMATION

The first step in valley formation is to lay a continuous valley blanket.



(6) PENETRATIONS

Sections cut out for roof penetrations (extractor pipes, roof windows, chimneys, etc.) should be kept as small as possible and the ends of the sheets must be fixed so that no rain or snow can penetrate. To achieve a perfect seal the suitable adhesive technology by ISOCELL GmbH & Co KG must be used. Make sure that the substrate is clean! The manufacturer can accept no liability for mechanical damage. The applicable regulations and guidelines (e.g. of the ZVDH (Central Association of German Roofers) for Germany, Austrian Standard, ÖNORM B 4119, for Austria, ...) must be observed! *The roof underlay does not replace roof covering. The roof must be covered during the period of the specified weathering time. Early covering has a positive effect on the resistance to ageing.*

