



KRENDL

The Innovator in Insulation Equipment

425 Machine

ANY JOB. ANY SIZE. ANY PLACE.



The 425 is a proven leader in the do-it-yourself rental market. Designed for low maintenance, rugged performance, and portability. Capable of blowing all major brands of cellulose and fiberglass to the manufacturer's specifications.

- Lightweight
- Larger hopper capacity
- Durable powder coat finish base. Molded polyethylene hopper.

Two Options:

8amp or 14amp / 2 stage blower


AMERICAN MADE.

Backed by a manufacturer's 2-YEAR WARRANTY

KRENDL MACHINE COMPANY • 1201 SPENCERVILLE RD. DELPHOS, OH 45833 • 800.459.2069 • F 419.695.9301



Electric Panel
LED start button
Audible alarm
Motor reset
Fuse Protection



Dual Agitators
Designed for constant
material flow

POWER REQUIREMENT

Single input, 15 amp / 120V / 60Hz CSA/CUL/UL
Double input, 15/15amps each / 120V / 60Hz CSA/CUL/UL

HOPPER CAPACITY

7 cu.ft. (.20m³)

WEIGHT/DIMENSIONS

220lbs / 34"W x 25"D x 44" H
100kg. / 86cm x 64cm x 112cm

MATERIAL PRODUCTION RATE

Single 8amp blower

Cellulose
1100 (499)*

Fiberglass
200 (91)*

Single 14amp blower

Cellulose
1400 (634)*

Fiberglass
480 (217)*

*Lbs/hr (kg/hr) rating with 100 ft. (30.5m)
of 2 1/2" (6.4cm) hose at 10ft (3.1m) elevation.

BLOWER SIZE

8 amp / 2-Stage (120V)
Blower system yields 104CFM @ 2 PSI or
14 amp / 2-Stage (120V)
Blower system yields 140CFM @ 3.5 PSI

AIRLOCK

14" x 8" diameter
35.6cm x 20.3cm diameter
2.5"(6.4cm) Outlet

ACCESSORIES

Machine includes corded remote
Optional accessories sold separately

425 PACKAGE

Part Numbers	Description	QTY
425-B	425 Machine	1
H318	2 1/2" x 50' Hose	2
339A	2 1/2"-3" Clamps	3
379	2 1/2" Connector	1
EXTCORD-B	100' Extension Cords	2

OTHER OPTIONAL ACCESSORIES

Part Numbers	Description	QTY
328	36" Hose Reel	1
425MK	425 Maintenance Kit	1

ADDITIONAL ACCESSORY OPTIONS AVAILABLE UPON REQUEST

Note: Manufacturer's product brand, density and variable blowing conditions will affect production rate.