

DECLARATION OF PERFORMANCE

1. Product code:

TREVEST 120 (50m x 3m)

2. Application:

Waterproofing membranes - Definition and properties of underlay and underlay membranes - Part 2: Underlay and underlay membranes for walls

3. Manufacturer:

**ALPIX COVER, Breite 29, 9450 Altstätten, Switzerland
Tel.: +49 71 755 68 29, info@alpix-cover.com**

4. Authorized representative:

not listed

5. AVCP-System:

System 3

6. Harmonized standard:

EN 13859-1:2010, EN 13850-2:2010

Identification number of the notified body:

**Institut pro testování a certifikaci a.s.,
Divize CSI - Centrum stavebního inženýrství.
Pražská 16, Praha 10, 102 21
Oznámený subjekt 1390**

7. Declared performance:

Key features	Performance			Harmonized technical specification
	Units	Nominal value	Tolerances	
Reaction to fire	[class]	E	-	EN 13859-1:2010, EN 13850-2:2010
Water Tightness class	[class]	W1	-	
Resistance to water tightness *	[class]	W1	-	
Wasserdampfdurchlässigkeit (sd-Value)	[m]	0,02	±30%	
Maximum tensile force MD/CD	[N/50mm]	305 / 180	±10%	
Maximum tensile force MD/CD after ageing *	[N/50mm]	80 / 80	±10%	
Elongation at break MD/CD				
Elongation at break MD/CD after ageing *	[%]	70 / 100	-	
Resistance to tear (nail shark) MD/CD	[%]	65 / 70	±10%	
Flexibility at low temperature	[N]	140 / 160	±10%	
Hazardous substances	[°C]	-40	-	
		none		

* - artificial ageing - UV 5000 h

8. Relevant technical documentation / specific technical documentation:

not issued

9. The performance of the product identified above is in conformity with the declared performance(s). This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified in point 3 above.

Signed for and on behalf of the manufacturer by:



Ute Langer
CEO

Altstätten, 01.08.2024