# DECLARATION OF PERFORMANCE

**1.** Product code:

## TREVEST 100 (50m x 1.5m)

**2.** Application:

**Waterproofing membranes - Definition and properties of underlay and underlay membranes - Part 2: Underlay and underlay membranes for walls**

**3.** Manufactuer:

**ALPIX COVER, Breite 29, 9450 Altstätten, Switzerland**
**Tel.: +49 71 755 68 29, info@alpix-cover.com**

**4.** Authorized representative:

**not listed**

**5.** AVCP-System:

**System 3**

**6.** Harmonized standard:

**EN 13859-1:2010, EN 13850-2:2010**

Identification number of the notified body:
**Institut pro testování a certifikaci a.s.,**
**Divize CSI - Centrum stavebního inženýrství.**
**Pražská 16, Praha 10, 102 21**
**Oznámený subjekt 1390**

**7.** Declared performance:

| Key features | Performance | | | Harmonized technical specification |
|---|---|---|---|---|
| | Units | Nominal value | Tolerances | |
| **Reaction to fire** | [class] | E | - | EN 13859-1:2010, EN 13850-2:2010 |
| **Water Tightness class** | [class] | W1 | - | |
| **Resistance to water tightness *** | [class] | W1 | - | |
| **Wasserdampfdurchlässigkeit (sd-Value)** | [m] | 0,02 | ±30% | |
| **Maximum tensile force MD/CD** | [N/50mm] | 200 / 100 | ±10% | |
| **Maximum tensile force MD/CD after ageing *** | [N/50mm] | 80 / 80 | ±10% | |
| **Elongation at break MD/CD** | [%] | 40 / 100 | - | |
| **Elongation at break MD/CD after ageing *** | [%] | 70 / 70 | ±10% | |
| **Resistance to tear (nail shark) MD/CD** | [N] | 105 / 140 | ±10% | |
| **Flexibility at low temperature** | [°C] | -40 | - | |
| **Hazardous substances** | | none | | |

* - artificial ageing - UV 5000 h

**8.** Relevant technical documentation / specific technical documentation:

**not issued**

**9.** The performance of the product identified above is in conformity with the declared performance(s). This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified in point 3 above.

Signed for and on behalf of the manufacturer by:

**Ute Langer**
CEO

Altstätten, 01.08.2024

**Manufactuer:** ALPIX COVER
Breite 29
9450 Altstätten
Switzerland

Tel.: +41 71 755 68 29
info@alpix-cover.com

# DECLARATION OF PERFORMANCE

**1.** Product code:

## TREVEST 100 (50m x 3m)

**2.** Application:

**Waterproofing membranes - Definition and properties of underlay and underlay membranes - Part 2: Underlay and underlay membranes for walls**

**3.** Manufactuer:

**ALPIX COVER, Breite 29, 9450 Altstätten, Switzerland**
**Tel.: +49 71 755 68 29, info@alpix-cover.com**

**4.** Authorized representative:

**not listed**

**5.** AVCP-System:

**System 3**

**6.** Harmonized standard:

**EN 13859-1:2010, EN 13850-2:2010**

Identification number of the notified body:
**Institut pro testování a certifikaci a.s.,**
**Divize CSI - Centrum stavebního inženýrství.**
**Pražská 16, Praha 10, 102 21**
**Oznámený subjekt 1390**

**7.** Declared performance:

| Key features | Performance | | | Harmonized technical specification |
|---|---|---|---|---|
| | Units | Nominal value | Tolerances | |
| **Reaction to fire** | [class] | E | - | EN 13859-1:2010, EN 13850-2:2010 |
| **Water Tightness class** | [class] | W1 | - | |
| **Resistance to water tightness *** | [class] | W1 | - | |
| **Wasserdampfdurchlässigkeit (sd-Value)** | [m] | 0,02 | ±30% | |
| **Maximum tensile force MD/CD** | [N/50mm] | 200 / 100 | ±10% | |
| **Maximum tensile force MD/CD after ageing *** | [N/50mm] | 80 / 80 | ±10% | |
| **Elongation at break MD/CD** | [%] | 40 / 100 | - | |
| **Elongation at break MD/CD after ageing *** | [%] | 70 / 70 | ±10% | |
| **Resistance to tear (nail shark) MD/CD** | [N] | 105 / 140 | ±10% | |
| **Flexibility at low temperature** | [°C] | -40 | - | |
| **Hazardous substances** | | none | | |

* - artificial ageing - UV 5000 h

**8.** Relevant technical documentation / specific technical documentation:

**not issued**

**9.** The performance of the product identified above is in conformity with the declared performance(s). This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified in point 3 above.

Signed for and on behalf of the manufacturer by:

**Ute Langer**
CEO

Altstätten, 01.08.2024

**Manufactuer:** ALPIX COVER
Breite 29
9450 Altstätten
Switzerland

Tel.: +41 71 755 68 29
info@alpix-cover.com

# DECLARATION OF PERFORMANCE

**1.** Product code:

**TREVEST 120 (50m x 1.5m)**

**2.** Application:

**Waterproofing membranes - Definition and properties of underlay and underlay membranes - Part 2: Underlay and underlay membranes for walls**

**3.** Manufactuer:

**ALPIX COVER, Breite 29, 9450 Altstätten, Switzerland**
**Tel.: +49 71 755 68 29, info@alpix-cover.com**

**4.** Authorized representative:

**not listed**

**5.** AVCP-System:

**System 3**

**6.** Harmonized standard:

**EN 13859-1:2010, EN 13850-2:2010**

Identification number of the notified body:
**Institut pro testování a certifikaci a.s.,**
**Divize CSI - Centrum stavebního inženýrství.**
**Pražská 16, Praha 10, 102 21**
**Oznámený subjekt 1390**

**7.** Declared performance:

| Key features | Performance | | | Harmonized technical specification |
|---|---|---|---|---|
| | Units | Nominal value | Tolerances | |
| **Reaction to fire** | [class] | E | - | EN 13859-1:2010, EN 13850-2:2010 |
| **Water Tightness class** | [class] | W1 | - | |
| **Resistance to water tightness *** | [class] | W1 | - | |
| **Wasserdampfdurchlässigkeit (sd-Value)** | [m] | 0,02 | ±30% | |
| **Maximum tensile force MD/CD** | [N/50mm] | 305 / 180 | ±10% | |
| **Maximum tensile force MD/CD after ageing *** | [N/50mm] | 80 / 80 | ±10% | |
| **Elongation at break MD/CD** | [%] | 70 / 100 | - | |
| **Elongation at break MD/CD after ageing *** | [%] | 65 / 70 | ±10% | |
| **Resistance to tear (nail shark) MD/CD** | [N] | 140 / 160 | ±10% | |
| **Flexibility at low temperature** | [°C] | -40 | - | |
| **Hazardous substances** | | none | | |

* - artificial ageing - UV 5000 h

**8.** Relevant technical documentation / specific technical documentation:

**not issued**

**9.** The performance of the product identified above is in conformity with the declared performance(s). This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified in point 3 above.

Signed for and on behalf of the manufacturer by:

**Ute Langer**
CEO

Altstätten, 01.08.2024

**Manufactuer:** ALPIX COVER
Breite 29
9450 Altstätten
Switzerland

Tel.: +41 71 755 68 29
info@alpix-cover.com

# DECLARATION OF PERFORMANCE

**1.** Product code:

## TREVEST 120 (50m x 3m)

**2.** Application:

**Waterproofing membranes - Definition and properties of underlay and underlay membranes - Part 2: Underlay and underlay membranes for walls**

**3.** Manufactuer:

**ALPIX COVER, Breite 29, 9450 Altstätten, Switzerland**
**Tel.: +49 71 755 68 29, info@alpix-cover.com**

**4.** Authorized representative:

**not listed**

**5.** AVCP-System:

**System 3**

**6.** Harmonized standard:

**EN 13859-1:2010, EN 13850-2:2010**

Identification number of the notified body:
**Institut pro testování a certifikaci a.s.,**
**Divize CSI - Centrum stavebního inženýrství.**
**Pražská 16, Praha 10, 102 21**
**Oznámený subjekt 1390**

**7.** Declared performance:

| Key features | Performance | | | Harmonized technical specification |
|---|---|---|---|---|
| | Units | Nominal value | Tolerances | |
| **Reaction to fire** | [class] | E | - | EN 13859-1:2010, EN 13850-2:2010 |
| **Water Tightness class** | [class] | W1 | - | |
| **Resistance to water tightness *** | [class] | W1 | - | |
| **Wasserdampfdurchlässigkeit (sd-Value)** | [m] | 0,02 | ±30% | |
| **Maximum tensile force MD/CD** | [N/50mm] | 305 / 180 | ±10% | |
| **Maximum tensile force MD/CD after ageing *** | [N/50mm] | 80 / 80 | ±10% | |
| **Elongation at break MD/CD** | [%] | 70 / 100 | - | |
| **Elongation at break MD/CD after ageing *** | [%] | 65 / 70 | ±10% | |
| **Resistance to tear (nail shark) MD/CD** | [N] | 140 / 160 | ±10% | |
| **Flexibility at low temperature** | [°C] | -40 | - | |
| **Hazardous substances** | | none | | |

* - artificial ageing - UV 5000 h

**8.** Relevant technical documentation / specific technical documentation:

**not issued**

**9.** The performance of the product identified above is in conformity with the declared performance(s). This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified in point 3 above.

Signed for and on behalf of the manufacturer by:

**Ute Langer**
CEO

Altstätten, 01.08.2024

**Manufactuer:** ALPIX COVER
Breite 29
9450 Altstätten
Switzerland

Tel.: +41 71 755 68 29
info@alpix-cover.com

# DECLARATION OF PERFORMANCE

**1.** Product code:

## TREVEST 120 WSK (50m x 1.5m)

**2.** Application:

**Waterproofing membranes - Definition and properties of underlay and underlay membranes - Part 2: Underlay and underlay membranes for walls**

**3.** Manufactuer:

**ALPIX COVER, Breite 29, 9450 Altstätten, Switzerland**
**Tel.: +49 71 755 68 29, info@alpix-cover.com**

**4.** Authorized representative:

**not listed**

**5.** AVCP-System:

**System 3**

**6.** Harmonized standard:

**EN 13859-1:2010, EN 13850-2:2010**

Identification number of the notified body:
**Institut pro testování a certifikaci a.s.,**
**Divize CSI - Centrum stavebního inženýrství.**
**Pražská 16, Praha 10, 102 21**
**Oznámený subjekt 1390**

**7.** Declared performance:

| Key features | Performance | | | Harmonized technical specification |
|---|---|---|---|---|
| | Units | Nominal value | Tolerances | |
| **Reaction to fire** | [class] | E | - | EN 13859-1:2010, EN 13850-2:2010 |
| **Water Tightness class** | [class] | W1 | - | |
| **Resistance to water tightness *** | [class] | W1 | - | |
| **Wasserdampfdurchlässigkeit (sd-Value)** | [m] | 0,02 | ±30% | |
| **Maximum tensile force MD/CD** | [N/50mm] | 305 / 180 | ±10% | |
| **Maximum tensile force MD/CD after ageing *** | [N/50mm] | 80 / 80 | ±10% | |
| **Elongation at break MD/CD** | [%] | 70 / 100 | - | |
| **Elongation at break MD/CD after ageing *** | [%] | 65 / 70 | ±10% | |
| **Resistance to tear (nail shark) MD/CD** | [N] | 140 / 160 | ±10% | |
| **Flexibility at low temperature** | [°C] | -40 | - | |
| **Hazardous substances** | | none | | |

* - artificial ageing - UV 5000 h

**8.** Relevant technical documentation / specific technical documentation:

**not issued**

**9.** The performance of the product identified above is in conformity with the declared performance(s). This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified in point 3 above.

Signed for and on behalf of the manufacturer by:

**Ute Langer**
CEO

Altstätten, 01.08.2024

**Manufactuer:** ALPIX COVER
Breite 29
9450 Altstätten
Switzerland

Tel.: +41 71 755 68 29
info@alpix-cover.com

# DECLARATION OF PERFORMANCE

**1.** Product code:

## TREVEST 150 WSK (50m x 1.5m)

**2.** Application:

**Waterproofing membranes - Definition and properties of underlay and underlay membranes - Part 2: Underlay and underlay membranes for walls**

**3.** Manufactuer:

**ALPIX COVER, Breite 29, 9450 Altstätten, Switzerland**
**Tel.: +49 71 755 68 29, info@alpix-cover.com**

**4.** Authorized representative:

**not listed**

**5.** AVCP-System:

**System 3**

**6.** Harmonized standard:

**EN 13859-1:2010, EN 13850-2:2010**

Identification number of the notified body:
**Institut pro testování a certifikaci a.s.,**
**Divize CSI - Centrum stavebního inženýrství.**
**Pražská 16, Praha 10, 102 21**
**Oznámený subjekt 1390**

**7.** Declared performance:

| Key features | Performance | | | Harmonized technical specification |
|---|---|---|---|---|
| | Units | Nominal value | Tolerances | |
| **Reaction to fire** | [class] | E | - | EN 13859-1:2010, EN 13850-2:2010 |
| **Water Tightness class** | [class] | W1 | - | |
| **Resistance to water tightness *** | [class] | W1 | - | |
| **Wasserdampfdurchlässigkeit (sd-Value)** | [m] | 0,02 | ±30% | |
| **Maximum tensile force MD/CD** | [N/50mm] | 300 / 220 | ±10% | |
| **Maximum tensile force MD/CD after ageing *** | [N/50mm] | 240 / 155 | ±10% | |
| **Elongation at break MD/CD** | [%] | 45 / 85 | - | |
| **Elongation at break MD/CD after ageing *** | [%] | 65 / 65 | ±10% | |
| **Resistance to tear (nail shark) MD/CD** | [N] | 165 / 200 | ±10% | |
| **Flexibility at low temperature** | [°C] | -40 | - | |
| **Hazardous substances** | | none | | |

* - artificial ageing - UV 5000 h

**8.** Relevant technical documentation / specific technical documentation:

**not issued**

**9.** The performance of the product identified above is in conformity with the declared performance(s). This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified in point 3 above.

Signed for and on behalf of the manufacturer by:

**Ute Langer**
CEO

Altstätten, 01.08.2024

**Manufactuer:** ALPIX COVER
Breite 29
9450 Altstätten
Switzerland

Tel.: +41 71 755 68 29
info@alpix-cover.com

# DECLARATION OF PERFORMANCE

**1.** Product code:

**TREVEST 150 (50m x 1.5m)**

**2.** Application:

**Waterproofing membranes - Definition and properties of underlay and underlay membranes - Part 2: Underlay and underlay membranes for walls**

**3.** Manufactuer:

**ALPIX COVER, Breite 29, 9450 Altstätten, Switzerland**
**Tel.: +49 71 755 68 29, info@alpix-cover.com**

**4.** Authorized representative:

**not listed**

**5.** AVCP-System:

**System 3**

**6.** Harmonized standard:

**EN 13859-1:2010, EN 13850-2:2010**

Identification number of the notified body:
**Institut pro testování a certifikaci a.s.,**
**Divize CSI - Centrum stavebního inženýrství.**
**Pražská 16, Praha 10, 102 21**
**Oznámený subjekt 1390**

**7.** Declared performance:

| Key features | Performance | | | Harmonized technical specification |
|---|---|---|---|---|
| | Units | Nominal value | Tolerances | |
| **Reaction to fire** | [class] | E | - | EN 13859-1:2010, EN 13850-2:2010 |
| **Water Tightness class** | [class] | W1 | - | |
| **Resistance to water tightness *** | [class] | W1 | - | |
| **Wasserdampfdurchlässigkeit (sd-Value)** | [m] | 0,02 | ±30% | |
| **Maximum tensile force MD/CD** | [N/50mm] | 300 / 220 | ±10% | |
| **Maximum tensile force MD/CD after ageing *** | [N/50mm] | 240 / 155 | ±10% | |
| **Elongation at break MD/CD** | [%] | 45 / 85 | - | |
| **Elongation at break MD/CD after ageing *** | [%] | 65 / 65 | ±10% | |
| **Resistance to tear (nail shark) MD/CD** | [N] | 165 / 200 | ±10% | |
| **Flexibility at low temperature** | [°C] | -40 | - | |
| **Hazardous substances** | | none | | |

* - artificial ageing - UV 5000 h

**8.** Relevant technical documentation / specific technical documentation:

**not issued**

**9.** The performance of the product identified above is in conformity with the declared performance(s). This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified in point 3 above.

Signed for and on behalf of the manufacturer by:

**Ute Langer**
CEO

Altstätten, 01.08.2024

**Manufactuer:** ALPIX COVER
Breite 29
9450 Altstätten
Switzerland

Tel.: +41 71 755 68 29
info@alpix-cover.com

# DECLARATION OF PERFORMANCE

**1.** Product code:

## VAPRO SD 15 (50m x 1.5m)

**2.** Application:

**Waterproofing membranes - plastic and elastomeric vapor barrier membrane**

**3.** Manufactuer:

**ALPIX COVER, Breite 29, 9450 Altstätten, Switzerland**
**Tel.: +49 71 755 68 29, info@alpix-cover.com**

**4.** Authorized representative:

**not listed**

**5.** AVCP-System:

**System 3**

**6.** Harmonized standard:

**EN 13984:2013**

Identification number of the notified body:
**Institut pro testování a certifikaci a.s.,**
**Divize CSI - Centrum stavebního inženýrství.**
**Pražská 16, Praha 10, 102 21**
**Oznámený subjekt 1390**

**7.** Declared performance:

| Key features | Performance | | | Harmonized technical specification |
|---|---|---|---|---|
| | Units | Nominal value | Tolerances | |
| **Reaction to fire** | [class] | E | - | EN 13984:2013 |
| **Water Tightness class** | [class] | W1 | - | |
| **Resistance to water tightness *** | [class] | W1 | - | |
| **Wasserdampfdurchlässigkeit (sd-Value)** | [m] | 15 | ±30% | |
| **Maximum tensile force MD/CD** | [N/50mm] | 160 / 130 | ±10% | |
| **Maximum tensile force MD/CD after ageing *** | [N/50mm] | - | ±10% | |
| **Elongation at break MD/CD** | [%] | 85 / 90 | - | |
| **Elongation at break MD/CD after ageing *** | [%] | - | ±10% | |
| **Resistance to tear (nail shark) MD/CD** | [N] | 130 / 150 | ±10% | |
| **Flexibility at low temperature** | [°C] | - | - | |
| **Hazardous substances** | | none | | |

* - artificial ageing - UV 5000 h

**8.** Relevant technical documentation / specific technical documentation:

**not issued**

**9.** The performance of the product identified above is in conformity with the declared performance(s). This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified in point 3 above.

Signed for and on behalf of the manufacturer by:

**Ute Langer**
CEO

Altstätten, 01.08.2024

**Manufactuer:** ALPIX COVER
Breite 29
9450 Altstätten
Switzerland

Tel.: +41 71 755 68 29
info@alpix-cover.com

# DECLARATION OF PERFORMANCE

**1.** Product code:

## VAPRO SD 15 (50m x 3m)

**2.** Application:

**Waterproofing membranes - plastic and elastomeric vapor barrier membrane**

**3.** Manufactuer:

**ALPIX COVER, Breite 29, 9450 Altstätten, Switzerland**
**Tel.: +49 71 755 68 29, info@alpix-cover.com**

**4.** Authorized representative:

**not listed**

**5.** AVCP-System:

**System 3**

**6.** Harmonized standard:

**EN 13984:2013**

Identification number of the notified body:
**Institut pro testování a certifikaci a.s.,**
**Divize CSI - Centrum stavebního inženýrství.**
**Pražská 16, Praha 10, 102 21**
**Oznámený subjekt 1390**

**7.** Declared performance:

| Key features | Performance | | | Harmonized technical specification |
|---|---|---|---|---|
| | Units | Nominal value | Tolerances | |
| **Reaction to fire** | [class] | E | - | EN 13984:2013 |
| **Water Tightness class** | [class] | W1 | - | |
| **Resistance to water tightness *** | [class] | W1 | - | |
| **Wasserdampfdurchlässigkeit (sd-Value)** | [m] | 15 | ±30% | |
| **Maximum tensile force MD/CD** | [N/50mm] | 160 / 130 | ±10% | |
| **Maximum tensile force MD/CD after ageing *** | [N/50mm] | - | ±10% | |
| **Elongation at break MD/CD** | [%] | 85 / 90 | - | |
| **Elongation at break MD/CD after ageing *** | [%] | - | ±10% | |
| **Resistance to tear (nail shark) MD/CD** | [N] | 130 / 150 | ±10% | |
| **Flexibility at low temperature** | [°C] | - | - | |
| **Hazardous substances** | | none | | |

* - artificial ageing - UV 5000 h

**8.** Relevant technical documentation / specific technical documentation:

**not issued**

**9.** The performance of the product identified above is in conformity with the declared performance(s). This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified in point 3 above.

Signed for and on behalf of the manufacturer by:

**Ute Langer**
CEO

Altstätten, 01.08.2024

**Manufactuer:** ALPIX COVER
Breite 29
9450 Altstätten
Switzerland

Tel.: +41 71 755 68 29
info@alpix-cover.com