



KRENDL

The Innovator in Insulation Equipment

475 Machine

ANY JOB. ANY SIZE. ANY PLACE.



The 475 is an economical machine for the professional contractor or a do-it-yourself rental market. Designed for low maintenance, rugged performance, and high production. Capable of blowing all major brands of cellulose and fiberglass to the manufacturer's specifications.

- Fold down loading door
- Removable all steel airlock allows for quick access for maintenance
- Lightweight
- User friendly electric dashboard
- Clear polycarbonate safety guard allows for easy inspection
- Durable powder coat finish
- Large 14 amp / 2 Stage blower
- Polyurethane flat free tires
- Built in tool holder

AMERICAN MADE.

Backed by a manufacturer's 2-YEAR WARRANTY

KRENDL MACHINE COMPANY • 1201 SPENCERVILLE RD. DELPHOS, OH 45833 • 800.459.2069 • F 419.695.9301



Electric Dashboard

LED start button - Digital hourmeter
Digital voltmeters - Variable blower speed control
Recessed power supply

POWER REQUIREMENT

Double input, 15/15amps each / 120V / 60Hz CSA/CUL/UL
International - Single input, 16 amp / 230V / 50Hz CE

HOPPER CAPACITY

14 cu.ft. (.39m³)
Loading made easy with built in adaptable tray

WEIGHT/DIMENSIONS

360lbs / 40.5"W x 31.5"D x 63" H
163kg / 103cm x 80cm x 160cm

BLOWER SIZE

14 amp / 2-Stage (120V)
Blower system yields 140CFM @ 3.5 PSI

AIRLOCK

12" x 10" diameter
30.5cm x 25.4cm diameter
3"(7.6cm) Outlet

ACCESSORIES

Machine includes corded remote
Optional accessories sold separately



Dual Agitators
Designed for constant material flow



Clear Safety Guard
Allows for easy inspection

MATERIAL PRODUCTION RATE

Cellulose
2100 (952)*

Fiberglass
700 (317)*

*Lbs/hr (kg/hr) rating with 150 ft. (45.8m) of 3" (7.6cm) hose at 16ft (4.8m) elevation.

475 PACKAGE

Part Numbers	Description	QTY
475DL	475 Machine	1
H319	3" x 50' Hose	3
339A	2 1/2"-3" Clamps	5
380	3" Connector	2
EXTCORD-B	100' Extension Cords	2

OTHER OPTIONAL ACCESSORIES

Part Numbers	Description	QTY
328	36" Hose Reel	1
KIT-641-12-24K	Wireless Remote	1
475MK	475 Maintenance Kit	1

ADDITIONAL ACCESSORY OPTIONS AVAILABLE UPON REQUEST

Note: Manufacturer's product brand, density and variable blowing conditions will affect production rate.