

VAPRO SD 15 (50M X 3M)

TECHNICAL DATASHEET

PRODUCT CODE **4058369311325**

DESCRIPTION



The VAPRO SD15 is a vapour barrier with an sd value of 12m. The vapour barrier is particularly easy to install and is intended for interior and roof extensions. In vapour barrier is intended for interior and roof construction. roof construction from moisture and draughts.

Color	white
Width (m)	3
Length (m)	50

Packaging Units	30 Rolls / Palett 4500 m ² / Palett
------------------------	---

DB = Vapour barrier

The values may be subject to tolerances. If not specified, the tolerance customary in the industry applies in accordance with the standard, material and property.



Revision: 23.02.24

VAPRO SD 15 (50M X 3M)

TECHNICAL VALUES	METHOD	VALUE	RESULT	TOLERANCES
Grammage	EN 1849-2	g/m ²	100	± 10 %
Reaction to fire	EN13501-1 EN 11925-2	Class	E	
Water Thightness class	EN 1928	Class	W1	
sd-Value	EN 12572	m	15	± 20 %
Temperature resistance		°C	-40 / +80	
Maximum tensile force MD/CD	EN 12311-1 EN 13859-1;2	N/50mm	160 / 130	± 10 %
Elongation at break MD/CD	EN 12311-1 EN 13859-1;2	%	85 / 90	± 10 %
Resistance to tear (nail shark) MD/CD	EN 12311-1 EN 13859-1;2	N	130 / 150	± 10 %
Dimensional stability MD/CD	EN 1107-2	%	<1	± 10 %
Flexibility at low temperature	EN 1107-2	%	n/v	
Maximum UV stability	-	Weeks	2	
Resistance to penetration of air	EN 12114 EN 13859-2	m ³ /(m ² h50Pa)	<0,01	
Visible defects	EN 1850-2		none	
Hazardous substances	-		none	
Maximum tensile force MD/CD after ageing	EN 13859-1;2 Annex C	N/50mm	n/v	± 10 %
Elongation at break MD/CD after ageing	EN 13859-1;2 Annex C	%	n/v	± 10 %
Resistance to water thightness after ageing	EN 13859-1;2 Annex C	Class	W1	± 10 %

The values may be subject to tolerances. If not specified, the tolerance customary in the industry applies in accordance with the standard, material and property.

